



Datasheet

UACC-Adapter-PoE-USBC+UACC-G4-DBP-Cable-USB-7M

## G4 Doorbell Pro PoE Adapter (7 m)



## UACC-Adapter-PoE-USBC

### Mechanical

Dimensions	Without cable: Ø30.4 x 95 mm (Ø1.2 x 3.7")
Weight	85 g (3 oz)
Enclosure material	Polycarbonate

### Hardware

Ports	(1) Input: RJ45 (1) Output: USB Type-C
Power method	PoE
Input rating	48VDC, 0.25A
Output rating	5VDC, 2A
ESD/EMP protection	Contact: ±4kV Air: ±8kV
Compatible devices	Camera G4 Instant (UVC-G4-INS) G4 DoorBell Pro (UVC-G4-Doorbell-Pro)
Operating temperature	-10 to 40° C (14 to 104° F)
Operating humidity	5 to 90% noncondensing
Certifications	CE, FCC, IC

## UACC-G4-DBP-Cable-USB-7M

### Specifications

Weight	326 g (11.5 oz)
Cable length	7 m (22.96 ft)
Cable color	White
Shielding type	Shielded twisted pair (STP)
Conductor wire gauge	(2) 19 AWG + (3) 30 AWG
Conductor type	Stranded copper
Jacket material	Thermoplastic elastomer (TPE)
Jacket diameter	4.8 mm (0.19 in)
Bend radius	Min. 19.2 mm (0.76 in)
Anti-crosstalk divider	No
Flam rating	VW-1 (UL1581)
Storage temperature	-40 to 85° C (-40 to 185° F)
Operating temperature	-20 to 60° C (-4 to 140° F)

